

SPIDER MULTI-CHANNEL ENCODER



Overview

The Spider is a 5-Channel encoder with four audio/video inputs. Each encoder can independently stream and/or record. The inputs can also be sent to the built-in program encoder that can switch or assemble the inputs into an on-the-fly picture-in-picture output stream and/or recording.

Lecture Capture and More


The program output encoder streams and/or records your video. Choose input 1 to 4 or one of the several side by side or picture in picture templates. Elegant fade or cut between inputs and templates

Stream and Record

Spider streams in industry standard H.264 format, compatible with DEVOS, Arcus, and most 3rd party streaming servers and services. Very flexible encoder settings allow you to tune your settings to your needs. Each of the five encoders also support a secondary stream, providing ABR for bandwidth-challenged and mobile viewers.

Receive Streams

In addition to physical HDMI inputs, Spider can receive live IP streams and act as a decoder. You can mix local audio/video inputs with received IP Streams and present them as switched program output.



System Specifications

- Max FPS 1920x1080p@300fps (4 HDMI inputs + Program)
- Compression
 Hardware H264 video
 Baseline/Main/High at rates up to 64Mbps
 Audio AAC-LC 32Kbps-384Jbosm 4 8kHz 16 bit
- Inputs- 4 HDMI, 3 x 3.5mm audio mini-jack
- Output- 1HDMI Multiview or Program
 1 HDMI Program, 1 3.5mm audio mini-jack
- Resolution

Input:

1920x1080 (P60/P50/P30/P25/P24/i60/i50) 1280x720 (P60/P50) 1280x1024 (P60) 1280x960 (P60), 1024x768 (P60), 800x600 (P60) 720X480 (P60/i60), 640x480 (P60), 720x576 (P50/i50) Output:

Resize Range from 160x120 to 1920x1080 (P60)

- Streaming Protocols
 RTMP Push, RTSP UDP/TCP, TS UDP Multicast, HLS
- ManagementWeb UI, DEVOS control integration
- Ports2x USB 2.0 for keyboard/mouse option1x USB 3.0 for recording storage
- Switches
 Power, Record, Stream, Snapshot, Full View,
 Quad View, Picture by Picture, Picture-In-Picture,
 Program, Full Screen 1, 2, 3, 4
- Recording Mode MP4, TS, AVI, MOV
- Power 12 VDC/2A; Power Supply 110/220 VAC, 20W

Companion Products

- DEVOS On-Prem, Cloud, Software License & Hybrid
- ARCUS Cloud eCDN
- Set Top Box

Specifications subject to change without notice. Contact Discover video for latest information. REV 11-2022